

# dektites® STOCK

the pacesetter in quality prefab roof products



245 eisenhower lane south • lombard, illinois 60148  
 630.705.1920 • 800.243.3018 • fax 630.705.1930  
 www.patecurbs.com • e-mail: sales@patecurbs.com

## standard construction

For use on metal roof panels, aluminum, copper, plastic, fiberglass, lead and wood. Flexible aluminum base conforms to any panel. -30 to +250 F temperature range. One piece construction will not crack or break. Pleated EPDM cone adjusts to any roof pitch. Pipe diameter markings are clearly indicated on the flexible cone in inches and millimeters for accurate fitting. Applications include plumbing, heating and air conditioning pipes and vents, electrical service entrances, etc.. Effectively flashes and isolates the pipe from building movement created by expansion, contraction and vibration. Designed for pipe diameters from 1/4" through 24".

p.o. no. \_\_\_\_\_  
 customer \_\_\_\_\_  
 \_\_\_\_\_  
 project \_\_\_\_\_  
 location \_\_\_\_\_  
 \_\_\_\_\_  
 architect \_\_\_\_\_  
 engineer \_\_\_\_\_

## dektites standard



## dektite requirements

quantity	dektite size	pipe diameter range	base diameter	fasteners required	sealant required	tag
<b>standard - gray - 250 degrees F</b>						
	<b>mini</b>	1/8" - 1"	3 5/8"	5	1/12 tube	
	<b>#1</b>	1/4" - 2"	4 3/4"	6	1/10 tube	
	<b>#2</b>	1 3/4" - 3"	6 1/4"	8	1/7 tube	
	<b>#3</b>	1/4" - 4"	7 3/4"	10	1/6 tube	
	<b>#4</b>	3" - 6"	9 1/4"	12	1/5 tube	
	<b>#5</b>	4" - 7"	10 3/4"	14	1/4 tube	
	<b>#6</b>	5" - 9"	13 1/2"	16	1/4 tube	
	<b>#7</b>	6" - 11"	14 1/2"	18	1/3 tube	
	<b>#8</b>	7" - 13"	16 1/2"	22	1/3 tube	
	<b>#9</b>	10" - 18"	25 3/8"	32	1/2 tube	